



# Tekskil Executive Speech Prompters

Whether you are a Politician, a CEO, or just want to give the best presentation possible, a Tekskil Executive Speech Prompter is your Presentations Best Friend

The Tekskil Executive Speech Prompter is ideal for live speeches or presentations made from a podium or a stage. Dual-display setup affords the presenter two script-reading locations, thus allowing for a very natural delivery. The LCD display panels, enclosed in robust machined metal enclosures, project upward onto panes of glass (beamsplitter) suspended on extendable poles. These screens are practically invisible to the audience and the flat screen floor monitors used to scroll the script are stationed low to the ground for less visibility.

**Tekskil Speech Prompters comes complete with:**

- LCD Prompter Monitor – 15", 17" or 22"
- 12 VDC Power Supply
- Stub adapter
- Three section Monopole
- Beamsplitter with variable angle Adjustor
- Drapery Support Rod
- Privacy Curtain

**What are the benefits of using an Executive Speech Prompter?**

- No pressure on the talent to memorize.
- Eliminates the need for notes or cue cards.
- Allows speaker to focus on style & delivery.
- Enables speaker to maintain eye contact and build rapport with the audience.
- Permits last minute changes to material
- Makes consistent delivery of complex material a snap.



Set up one of our systems in your facility and see the difference for yourself

	15E	15P	17E	17P	22P
Panel Type:	High Bright Active Matrix TFT LCD				
Diagonal Screen Size (HxV):	15.0 inches (11.7" x 9")	15.0 inches (11.7" x 9")	17.0 inches (13.3" x 10.6")	17.0 inches (13.3" x 10.6")	22.1 inches (18.7" x 11.7")
Pixel Format (RGB):	1024 x 768	1280 x 1024	1280 x 1024	1280 x 1024	1680 x 1050
Backlight Type:	CCFL	LED	CCFL	LED	LED
Backlight Brightness:	850 cd/m <sup>2</sup> (nits)	1600 cd/m <sup>2</sup> (nits)	850 cd/m <sup>2</sup> (nits)	1200 cd/m <sup>2</sup> (nits)	1200 cd/m <sup>2</sup> (nits)
Contrast Ratio:	600:1	1000:1	600:1	1000:1	1000:1
Viewing Angle (H/V):	140° / 120°	170° / 170°	140° / 120°	170° / 170°	170° / 170°
Lamp Life:	10,000 hrs.	60,000 hrs.	10,000 hrs.	60,000 hrs.	60,000 hrs.
Power Consumption:	38 W	28 W	43 W	28 W	34 Watts
Warranty:	Three Years	Five Years	Three Years	Five Years	Five Years

**Tekskil Industries, Inc.**