



<h2>Prompter Selection Guide</h2> <p>877-TEKSKIL Tekskil.com</p>	520-PT Load: 70 lbs.		600-PT Load: 120 lbs.		700-PT Load: 200 lbs.		
							
Specifications	15ER Prompter	17ER Prompter	17E Prompter	17P Prompter	19SE Prompter	19SP Prompter	22P Prompter
Brightness (cd/m <sup>2</sup> )	700	700	700	1000	700	1000	1200
Contrast Ratio	2000:1	2000:1	2000:1	2000:1	2000:1	2000:1	2000:1
Power Consumption (12 VDC)	28 Watts	40 Watts	40 Watts	45 Watts	40 Watts	45 Watts	50 Watts
Panel Weight	7 lbs.	9 lbs.	12 lbs.	12 lbs.	14 lbs.	14 lbs.	16 lbs.
Warranty	3 Years	3 Years	3 Years	5 Years	3 Years	5 Years	5 Years
<b>Prompter Options</b>	<b>Beamsplitters</b>						
	Standard 16:9 HD lens	✓	✓	✓	✓	✓	--
	Wide Angle 16:9 HD lens	--	--	✓	✓	✓	✓
	<b>Tally Option</b>						
	Front mount single-stage 3x3 LED cluster	✓	✓	✓	✓	✓	✓
	Top mount dual-stage LED bars & Cam #	✓	✓	✓	✓	✓	✓
	<b>Timing Option</b>						
	6 digit VITC SMPTE clock 2.3" high LEDs	✓	✓	✓	✓	✓	✓
	<b>Aux/Talent Assist Monitors</b>						
	19" LED Edge-lit 16:9	--	--	✓	✓	✓	✓
22" LED Edge-lit 16:9	--	--	--	--	✓	✓	

Tekskil Displays feature: Sophisticated power management to prevent image distortion, electrical noise and display damage  
Signal conditioning to eliminate ground loops and drop-outs  
Temperature control elements, including twin cooling fans to prevent image loss, back light failure and circuitry overheats

Tekskil Prompting Systems feature: Integrated stabilization and dampening elements to minimize prompter vibration and lurching during camera movement  
Micro-truss construction provides optimal strength, balance and weight for **greatly** reduced pan/tilt servo stress and failure.