

Prompter Selection Guide

877-TEKSKIL
Tekskil.com

Tekskil Displays feature:

- Sophisticated power management to prevent image distortion, electrical noise and display damage.
- Signal conditioning to eliminate ground loops and drop-outs.
- Temperature control elements, including twin cooling fans to prevent image loss, back light failure and circuitry overheats

Tekskil Prompting Systems feature:

- Integrated stabilization and dampening elements to minimize prompter vibration and lurching during camera movement
- Micro-truss construction provides optimal strength, balance and weight for **greatly** reduced pan/tilt servo stress and failure



VR-600
Load: 70 lbs.



Specifications	17E Prompter	17P Prompter	19SE Prompter	19SP Prompter
Brightness (cd/m ²)	700	1000	700	1000
Contrast Ratio	2000:1	2000:1	2000:1	2000:1
Power Consumption (12 VDC)	40 Watts	45 Watts	40 Watts	45 Watts
Panel Weight	12 lbs.	12 lbs.	14 lbs.	14 lbs.
Warranty	3 Years	5 Years	3 Years	5 Years

Prompter Options	Beamsplitters				
	Standard 16:9 HD lens	✓	✓	✓	✓
	Wide Angle 16:9 HD lens	✓	✓	✓	✓
	Tally Option				
	Front mount single-stage 3x3 LED cluster	✓	✓	✓	✓
	Top mount dual-stage LED bars & Cam ID #	✓	✓	✓	✓
	Timing Option				
	6 digit VITC SMPTE clock 2.3" high LEDs	✓	✓	✓	✓
	Aux/Talent Assist Monitor				
	19" LED Edge-lit 16:9 w/HDMI Video Input	✓	✓	✓	✓