



Tekskil Executive Speech Promoters

Whether you are a Politician, a CEO, or just want to give the best presentation possible, a Tekskil Executive Speech Prompter is your Presentations Best Friend

The Tekskil Executive Speech Prompter is ideal for live speeches or presentations made from a podium or a stage. Dual-display setup affords the presenter two script-reading locations, thus allowing for a very natural delivery. The LCD display panels, enclosed in robust machined metal enclosures, project upward onto panes of glass (beamsplitter) suspended on extendable poles. These screens are practically invisible to the audience and the flat screen floor monitors used to scroll the script are stationed low to the ground for less visibility.

Tekskil Speech Promoters comes complete with:

- LCD Prompter Monitor – 17" or 19" and 700 or 1000 Nits LED Backlight
- 12 VDC Power Supply
- Stub adapter
- Three section Monopole
- Beamsplitter with variable angle Adjustor
- Drapery Support Rod
- Privacy Curtain

What are the benefits of using an Executive Speech Prompter?

- No pressure on the talent to memorize.
- Eliminates the need for notes or cue cards.
- Allows speaker to focus on style & delivery.
- Enables speaker to maintain eye contact and build rapport with the audience.
- Permits last minute changes to material
- Makes consistent delivery of complex material a snap.



17E-SP shown without Privacy Curtain

	17E	17P	19SE	19SP
Panel Type:	TFT LCD High Bright Panel			
Diagonal Screen Size (HxV):	17.0 inches (13.3" x 10.6")	17.0 inches (13.3" x 10.6")	19.0 inches (14.8" x 11.9")	19.0 inches (14.8" x 11.9")
Pixel Format (RGB):	1280 x 1024	1280 x 1024	1280 x 1024	1280 x 1024
LED Backlight Brightness:	700 cd/m ² (nits)	1000 cd/m ² (nits)	700 cd/m ² (nits)	1000 cd/m ² (nits)
Contrast Ratio:	2000:1	2000:1	2000:1	2000:1
Viewing Angle (H/V):	140° / 120°	170° / 170°	150° / 150°	150° / 150°
Lamp Life:	60,000 hrs.	60,000 hrs.	60,000 hrs.	60,000 hrs.
Panel Weight:	12.0 lbs.	12.0 lbs.	14.0 lbs.	14.0 lbs.
Power Consumption:	30 Watts (12 VDC)	38 Watts (12 VDC)	44 Watts (12VDC)	47 Watts (12 VDC)
Warranty:	Three Years	Five Years	Three Years	Five Years

Set up one of our systems in your facility and see the difference for yourself

Tekskil Industries, Inc.