



# Tekskil Network Integrated PTZ Camera Prompter Systems

**Tekskil's Network Integrated Power Pedestal / Prompter Capsule transforms your PTZ camera into a robust Studio Camera Platform**



### PTZ26 Prompter Capsule (Q30)

- Houses the PTZ camera
- 70:30 panoramic beamsplitter
- 24-foot field of view at 10-foot distance

### 19SE-T Prompter Monitor (D17)

- 19" Premium display
- Custom heat and power control
- Composite video input
- 3G/HD/SDI video input

### Floor Manager (TA40)

- 3-stage tally (Preview/Program/Special)
- Selectable Camera ID (0 - 99)
- Clock, Count-down & Count-up timer
- Ad hoc messaging
- Tekskil Network Control application

### Talent Display (TA35)

- 19" 12 VDC LED backlit display
- Composite / HDMI video input
- 3G/HD/SD-SDI video input

### Network Control

- Wireless Control from local Tablet, Smartphone or Laptop Computer
- Optional Network Hub for Panasonic AW-RP150 PTZ Controller Interface

### Power Pan (Pan370)

- 75-pound payload
- 370-degree rotation range
- Absolute Positioning
- Local control with 3 position memory
- Optional Tethered Control
- Optional Network Control with expanded functions and 12 additional memory presets

### Power Pedestal (Ped319)

- 75-pound payload
- 19-inch elevation range
- Absolute Positioning
- Local control with 3 position memory
- Built-in Power Distribution (AC & DC)
- Optional Pan Bar Kit
- Optional Tethered Control
- Optional Network Control with expanded functions and 12 additional memory presets

Specifications	19SE-T Performance Series (D17)
Diagonal Screen Size (H x V):	19 inches (14.8" x 11.9")
Pixel Format (RGB):	1280 x 1024 (Native)
LED Backlight Brightness:	1000 cd/m <sup>2</sup> (≈ 1000 Nits)
Contrast Ratio:	2000:1
Viewing Angle (H/V):	150° / 150° minimum
Video (CVBS) Input:	BNC (x1)
3G/HD/SD-SDI Input:	BNC (x1)
Display Weight:	9 lbs.
LED Lamp Life:	80,000+ hours
12 VDC Input:	XLR 4-Pin Male
Power Consumption:	40 Watts at full brightness
Warranty:	3 Years

More and more stations are adopting automation for improved production and reduced costs. A new breed of integrated pan/tilt/zoom cameras has emerged - PTZs. Utilizing miniature pan tilt assemblies with compact high performance cameras, PTZ systems provide broadcast quality video at a very reasonable cost. However, they come with a headache – how do you integrate a teleprompter for the talent? And how do you communicate to the talent when the Cameraman is in the Control Room? Tekskil fills this need with the development of the Network Integrated Prompter System.

**Set up one of our systems in your studio and see the difference for yourself**

## Tekskil Broadcast Products

Toll Free: 877-TEKSKIL (835-7545)  
Visit our website at [Tekskil.com](http://Tekskil.com)

Toll Free Fax: 877-576-8361  
Email: [Team@tekstil.com](mailto:Team@tekstil.com)



# Tekskil Networked Integrated PTZ System Ethernet Flow Diagram



From Network

Panasonic AW-RP150  
(Typical)

Tekskil Network Hub

N11 Pedestal

19" Prompter Monitor

N12 Pan Table

FM Cam ID (0-99)

FM Tally (3-Stage)

FM Clock/Timer

FM Ad Hoc Message

AW-UE150 PTZ Camera



N11 Pedestal

19" Prompter Monitor

N12 Pan Table

FM Cam ID (0-99)

FM Tally (3-Stage)

FM Clock/Timer

FM Ad Hoc Message

AW-HN130 PTZ Cam



N11 Pedestal

19" Prompter Monitor

N12 Pan Table

FM Cam ID (0-99)

FM Tally (3-Stage)

FM Clock/Timer

FM Ad Hoc Message

AW-UN70 PTZ Cam



To Other Network PTZ Systems