



# Tekskil 19 inch Replacement Prompter Monitors

## See why Tekskil Replacement Monitors can save you money

**Reliability:** Most LCD prompting systems in use today are more than six years old, and, unlike fine wine, they do not get better with age. High voltage breakdown in the inverters, poor contrast, and fading lamps add up to a prompter your talent strains to read. First and second generation LCD panels are failing because of old backlight technology causing loss of contrast and very low brightness. Tekskil Replacement Monitors incorporate a high bright LED backlit display with twin cooling fans and DC power management, all housed in a rugged welded aluminum enclosure.



**Features:** Enhanced contrast and panel brightness provide a crisp, easy to read talent display. Available in *Basic* (550+ Nits) and *Premium* (1000+ Nits) versions both with 2000:1 Contrast Ratio. 3G/SD/HD-SDI and Composite (CVBS) Video Inputs are standard.

**Installation:** A Tekskil Replacement Monitor can be mounted on your existing prompting system – regardless of brand. Every replacement prompting head has the correct mounting hardware built in for simple replacement of those failing displays sold by other prompter companies.

**Cost:** Tekskil Replacement Monitors are half the cost (or less) of those lower performance displays offered by other brands, supported by a 3 year warranty.

**Options:**

- 12 VDC 5.0 Amp Power Supply (DG13)
- Dimmable front mounted LED Tally Array (TA90)
- TallyCAM Dual Tally 'Red/Amber' with Camera ID '0-19' (TA96+)

19 inch Replacement Monitor Specifications		
	19B	19P
Diagonal Screen Size (H x V):	19 inches (14.8" x 11.9")	19 inches (14.8" x 11.9")
Pixel Format (RGB):	1280 x 1024 (Native)	1280 x 1024 (Native)
LED Backlight Brightness:	550+ cd/m <sup>2</sup> (approx 550 Nits)	1000+ cd/m <sup>2</sup> (approx 1000 Nits)
Contrast Ratio:	2000:1	2000:1
Viewing Angle (H/V):	150° / 150° minimum	170° / 170° minimum
Composite Video (CVBS) Input:	BNC (x1)	BNC (x1)
3G/SD/HD-SDI Input:	BNC (x1)	BNC (x1)
Display Weight:	8 lbs.	8 lbs.
LED Lamp Life:	60,000+ hours	60,000+ hours
12 VDC Input:	Industry Standard XLR 4-Pin Male	Industry Standard XLR 4-Pin Male
Power Consumption:	40 W @ full brightness	45 W @ full brightness
Warranty:	3 year	3 year

**Tekskil Quality Engineered for your Studio**

**Tekskil Broadcast Products**

Toll Free Phone: 877-TEKSKIL (835-7545)

Website: [Tekskil.com](http://Tekskil.com)

Toll Free Fax: 877 576-8361

Email: [Team@tekstil.com](mailto:Team@tekstil.com)