



# Tekskil Network Integrated PTZ Camera Prepositioning Robotic Prompter System

## Tekskil's Network Integrated Power Pedestal / Prompter Capsule transforms your PTZ camera into a robust Studio Camera Platform

### PTZ26 Prompter Capsule (Q30)

- Houses the PTZ camera
- 70:30 panoramic beamsplitter
- 24-foot field of view at 10-foot distance

### 19P-T Prompter Monitor (D17)

- 19" Premium display
- Custom heat and power control
- Composite video input
- 3G/HD/SDI video input
- Optional Network Interface for IP feeds

### Floor Manager (TA40)

- 3-stage tally (Preview/Program/Special)
- Alphanumeric Selectable Camera ID
- Clock, Dual Count-down & Count-up timers
- Ad hoc messaging
- Tekskil Network Control application

### Talent Display (TA38)

- 19" LED backlit display
- Composite / HDMI video input
- 3G/HD/SD-SDI video input

### Network Control

- Wireless Control from local Tablet, Smartphone or Laptop Computer
- Network Control Hub/Proxy Server for Panasonic AW-RP150 PTZ Controller



### Power Pan (Q40)

- 90-pound payload
- 370-degree rotation range
- Absolute Positioning
- Local control with 3 position memory
- Optional Tethered Control (Q51)
- Optional Network Control with expanded functions and 100 memory presets

### Power Pedestal (Q50)

- 90-pound payload
- 19-inch elevation range
- Absolute Positioning
- Local control with 3 position memory
- Built-in Power Distribution (AC & DC)
- Optional Pan Bar Kit (Q52)
- Optional Tethered Control (Q51)
- Network Control with expanded functions and 100 memory presets

Specifications	19P-T Performance Series (D17)
<b>Diagonal Screen Size (H x V):</b>	<b>19 inches (14.8" x 11.9")</b>
<b>Pixel Format (RGB):</b>	<b>1280 x 1024 (Native)</b>
<b>LED Backlight Brightness:</b>	<b>1000 cd/m<sup>2</sup> (≈ 1000 Nits)</b>
<b>Contrast Ratio:</b>	<b>2000:1</b>
<b>Viewing Angle (H/V):</b>	<b>170° / 170° minimum</b>
<b>Video (CVBS) Input:</b>	<b>BNC (x1)</b>
<b>3G/HD/SD-SDI Input:</b>	<b>BNC (x1)</b>
<b>Display Weight:</b>	<b>9 lbs.</b>
<b>LED Lamp Life:</b>	<b>80,000+ hours</b>
<b>12 VDC Input:</b>	<b>XLR 4-Pin Male</b>
<b>Power Consumption:</b>	<b>40 Watts at full brightness</b>
<b>Warranty:</b>	<b>1 Year</b>

More and more stations are adopting automation for improved production and reduced costs. A new breed of integrated pan/tilt/zoom cameras has emerged - PTZs. Utilizing miniature pan tilt assemblies with compact high performance cameras, PTZ systems provide broadcast quality video at a very reasonable cost. However, they come with a headache – how do you integrate a teleprompter for the talent? And how do you communicate to the talent when the Cameraman is in the Control Room? Tekskil fills this need with the development of the Integrated Network Teleprompter System.

**Tekskil Quality Engineered for your Studio**

**Tekskil Broadcast Products**