



Network Integrated Prepositioning PTZ Teleprompter Talent Assist Solution

Powerful Automation Platform for your Studio PTZ Cameras

More and more stations are adopting automation for improved production and reduced costs. A new breed of integrated pan/tilt/zoom cameras has emerged - PTZs. Utilizing miniature pan tilt assemblies with compact high performance cameras, PTZ systems provide broadcast quality video at a very reasonable cost. However, they come with a headache – how do you integrate a teleprompter for the talent? And how do you communicate to the talent when the Cameraman is in the Control Room? Tekskil fills this need with the development of the affordable Network Integrated Teleprompter System – combining a motorized Pedestal, motorized Pan Table, PTZ Camera Capsule with 19 inch Premium Teleprompter, Talent Assist/Aux Monitor, and the all-inclusive Electronic Floor Manager all controlled by a single CAT-6A network cable.

PTZ26 Prompter Capsule (Q30)

- Houses the PTZ camera
- 70:30 panoramic beamsplitter
- 24-foot field of view at 10-foot distance

19SE-T Prompter Monitor (D17)

- 19" Premium display
- Custom heat and power control
- Composite video input
- 3G/HD/SDI video input
- DC Power Distribution for accessories

Electronic Floor Manager (TA40)

- 3-stage tally (Preview/Program/Special)
- Selectable Camera ID (1 – 99, A1 – Z9)
- Clock, 12/24 Hour display
- Dual Count-up and Count-down Timers
- Ad hoc messaging
- All functions feature user defined colors
- Tekskil Network Control application

Talent Assist/Aux Display (TA39)

- 21.5" 12 VDC LED backlit display
- Composite video input
- 3G/HD/SD-SDI video input

Network Control Hub/Server

- Wireless Control from local Tablet or Laptop Computer with Touchscreen
- Network Control Hub/Proxy Server for Panasonic and Sony PTZ Cameras
- Graphical User Interface for enhanced features and control
- Optional "Orchestrator" Server



Q30-PTZ-6P "Full Meal Deal"
System shown

Test Monitor/Viewfinder (TA37P)

- 7" Premium display
- 3G/HD-SDI and HDMI video inputs with cross conversion
- Test Functions – YRGB Column Display, Waveform and Vectorscope, Peaking, False Color, and Histogram

Power Pan Table (Q45)

- 90-pound payload
- ±185° rotation range
- Absolute Positioning
- Local control with 3 position memory
- Tethered Remote Control
- Optional Network Control with 100 memory presets

Power Pedestal (Q65)

- 90-pound payload
- 19-inch elevation range
- Absolute Positioning
- Local control with 3 position memory
- Built-in Power Distribution (AC & DC)
- Custom engineered coiled cords for tangle free operation
- Junction Box built into pedestal leg for single point studio interconnection
- Pan Bar Kit
- Tethered Remote Control
- Optional Network Control with 100 memory presets and expanded functions

TEKSKIL ENGINEERED QUALITY FOR YOUR STUDIO

Tekskil Broadcast Products

Toll Free: 877-TEKSKIL (835-7545)
Visit our website at Tekskil.com

Toll Free Fax: 877-576-8361
Email: Team@tekstil.com